COLUMBIA CITY CARRIER ANNEX **3613 SOUTH JUNEAU STREET SEATTLE, WASHINGTON 98118**

BID SET

GENERAL NOTES

- DRAWINGS: THE DRAWINGS ARE INTENDED TO DESCRIBE THE OVERALL SCOPE OF WORK CONTRACTORS SHALL FIELD VERIFY EXISTING CONDITIONS AND ALERT OWNER TO ANY UNFORESEEN CONSTRUCTION DIFFICULTIES BEFORE BEGINNING WORK.
- REPETITIVE ITEMS: TYPICAL WALL SECTIONS, FINISHES, AND DETAILS ARE NOT INDICATED EVERYWHERE THEY OCCUR ON PLANS, ELEVATIONS AND SECTIONS. REFER TO DETAIL DRAWINGS. CONTRACTOR TO PROVIDE AS IF DRAWN IN FULL.
- CODES / PERMITS / REGULATIONS: CONTRACTOR SHALL OBTAIN AND PAY FOR A PERMITS NECESSARY. A BUILDING PERMIT IS REQUIRED. CONTRACTOR SHALL ALSO PAY FOR ALL OTHER CHARGES, FEES OR COSTS CHARGED BY UTILITY AGENCIES OR PRIVATE COMPANIES WHICH REQUIRE SUCH COSTS FOR OR PRIOR TO INSTALLATIONS. INCLUDE

NOTHING IN THE DRAWINGS SHALL BE CONSTRUED TO PERMIT AN INSTALLATION IN VIOLATION OF APPLICABLE CODES AND/OR RESTRICTIONS. SHOULD ANY CHANGE IN THE DRAWINGS BE NECESSARY IN ORDER TO COMPLY WITH APPLICABLE CODES AND/OR REQUIREMENTS, THE CONTRACTOR SHALL NOTIFY THE OWNER AT ONCE. ALL PARTS PERFORMED UNDER THIS CONTRACT SHALL BE IN FULL ACCORDANCE WITH THE LATEST RULES. REGULATIONS. RESTRICTIONS. REQUIREMENTS AND CODES.

ALL WORK SHALL CONFORM TO THE 2009 IBC & MECHANICAL CODES. AND ALL LOCAL

- <u>DIMENSIONS</u>; DIMENSIONS ARE SHOWN TO FACE OF STUD UNLESS DETAILED OTHERWISE
- EXISTING ITEMS: ON ELEVATIONS, PLANS & DETAIL DRAWINGS ANY ITEM NOT CALLED OUT AS "EXISTING" OR INDICATED AS "(E)" SHALL BE ASSUMED TO BE NEW.
- OCCUPANT & PEDESTRIAN PROTECTIONS: BUILDING WILL BE OCCUPIED DURING THE WORK. CONTRACTOR SHALL MAINTAIN OVERHEAD PROTECTION WHERE AN OVERHEAD
- INTERIOR PROTECTIONS, DUST CONTROL & HOUSEKEEPING: PRIOR TO COMMENCING, CONTRACTOR SHALL PROTECT INTERIOR SPACES AGAINST DUST, DEBRIS & OVERHEAD FALLING HAZARD BY INSTALLATION OF PLYWOOD BARRIERS & POLY SHEETING OR OTHER METHODS THAT PERMIT OCCUPANTS TO MAINTAIN NORMAL ACTIVITIES AS MUCH AS POSSIBLE DURING THE WORK.
- ODOR CONTROL: CONTRACTOR SHALL TAKE ALL PRECAUTIONS TO MINIMIZE IMPACT OF ODOR-CAUSING OPERATIONS ON BUILDING OCCUPANTS. CONTRACTOR SHALL NOTE LOCATION OF BUILDING AIR INTAKES & BE PRO-ACTIVE IN ARRANGING FOR SHUT-DOWN, FILTERING, OFF-HOUR WORK OR OTHER MEANS OF CONTROL. SCHEDULE ALL ACTIVITIES
- NOISE CONTROL: CONTRACTOR SHALL SCHEDULE ANY EXCESSIVE NOISE PRODUCING ACTIVITIES (SUCH AS CORE DRILLING AND CONCRETE CUTTING) FOR EARLY MORNING, EVENING OR WEEKEND HOURS.

OCCUR DURING NORMAL DAYTIME WORK HOURS.

DETAIL NO.

SHEET NO

DETAIL REFERENCE

DETAIL REFERENCE AT

THROUGH WALL

BASE OF WALL

REFERENCE

BUILDING ACCESS & WORK HOURS: CONTRACTOR ACCESS TO BUILDING FOR WORK SHALL

REFERENCE SYMBOLS

ABBREVIATIONS

ACOUSTICAL CLG. PANEL LOCATION ABOVE FINISHED FLOOR MAXIMUM ARCHITECTURAL MTL METAL MINIMUM BICYCLE RACK MASONRY JOINT COUNTERFLASHING NOT IN THIS CONTRACT

NTS

PLYWD

S.A.M.

STOR

STRUCT

SPEC, SPECS

SEAL

CONTROL JOINT

CONCRETE BLOCK

CENTER LINE

CEILING

CONCRETE

CONSTRUCTION

CONTINUOUS

DOCK BUMPERS

DOOR OPENING

DIAMETER

DIMENSION

DOWNSPOUT

DRAWING

ELEVATION

EXTERIOR

EXPANSION JOINT

EXIST, EXISTING

FACTORY FINISH

FINISH FLOOR

FLASHING

F00T

GAUGE

GLASS

HEIGHT

INSULATION

INTERIOR

GALVANIZED

GRAB BAR

GLU-LAM BEAM

HOLLOW METAL

GYPSUM WALLBOARD

FIRE ALARM PANEL

CONC

CONT

ELEV

(E), E.

FLSHG

GALV

INSUL

WALL SECTION

REFERENCE

REFERENCE

KEY NOTE

FLAG NOTE INDICATING

QUANTITY

DIRECTION OF

X/AXX

EJ

- NUMBER NOT TO SCALE OUTSIDE DIMENSION OPPOSITE HAND
 - POWDER COAT PERFORATED PLYWOOD PREFINISHED PRESSURE TREATED
 - RISER, RADIUS ROOM, ROOMS ROUGH OPENING
 - SELF-ADHESIVE FLASHING SELF-ADHESIVE MEMBRANE SEALED CONCRETE SQUARE FEET SAFETY GLAZING SIMIL AR SPECIFICATIONS STAINLESS STEEL
 - STEEL STORAGE STRUCTURAL SUSPENDED TOOLED JOINT TYPICAL

WEATHER RESISTIVE BARRIER

WATER CLOSET

WATERPROOFING

PROJECT INFORMATION

CODES USED:

2015 INTERNATIONAL BUILDING CODE WAC 51-50 2015 INTERNATIONAL MECHANICAL CODE WAC 51-52 2015 INTERNATIONAL FIRE CODE WAC 51-54 2015 UNIFORM PLUMBING CODE WAC 51-56, 51-57 2015 WASHINGTON STATE ENERGY CODE WAC 51-11 ICC A117.1-2017 ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES

BUILDING INFORMATION:

NAME: COLUMBIA CITY CARRIER ANNEX

SITE ADDRESS: 3613 SOUTH JUNEAU STREET, SEATTLE, WA 98118

PARCEL NUMBER: 222404-9009

POR OF N 1/2 OF NE 1/4 OF SW 1/4 OF SW 1/4 LY S OF JUNEAU ST & ELY OF EMPIRE WAY LESS E 20 FT LESS POR FOR CPSRTA R/W TAKE PER REC #20040309002701

CONSTRUCTION TYPE: VB

OCCUPANCY: B

BUILDING AREA: 11,720 SF (EXISTING) PLATFORM: 1,007 SF OCCUPANCY: B (BUSINESS)

SITE AREA: 48,693 SF (1.12 ACRES)

OCCUPANCY LOAD: 11,720 SF / 100 = 117

BLDG. HEIGHT = 20'-0" (EXISTING)

FULLY SPRINKLERED FIRE ALARM

CONSULTANTS

LANDSCAPE ARCHITECT

TERRAFORMA DESIGN GROUP

5027 51ST AVENUE SW

SEATTLE, WA 98136

(206) 923-0590

AKEMI SAKAIDA

<u>ARCHITECT</u> CORNERSTONE ARCHITECTURAL GROUP 6161 NE 175TH STREET, SUITE 101 KENMORE, WA 98028 TEL: (206) 682-5000

STRUCTURAL

STEVE BAŔNES

PSM CONSULTING ENGINEERS 2200 6TH AVENUE, SUITE 601 SEATTLE, WA 98121 TEL: (206) 622-4580 DAVID STUBBS

<u>MECHANICAL</u>

1111 FAWCETT AVENUE, SUITE 100 TACOMA, WA 98402 TEL: (253) 383-3283 RICK HULTZ

ELECTRICAL

HULTZ BHU 1111 FAWCETT AVENUE, SUITE 100 TACOMA, WA 98402 TEL: (253) 383-3283 TOM URQUHART

TERRAFORMA DESIGN GROUP, INC. 5027 51ST AVENUE SW SEATTLE, WA 98136 (206)923-0590 PEDRO DEGUZMAN

INDEX OF DRAWINGS

TITLE SHEET

CIVIL SITE PLAN C1.2 EROSION CONTROL PLAN C1.3 GRADING & DRAINAGE PLAN

C1.4 UTILITY PLAN C1.5 CIVIL DETAILS C1.6 CIVIL DETAILS CIVIL DETAILS

C1.8 CIVIL DETAILS LANDSCAPE PLAN

SITE DETAILS A1.2

A1.3 SITE DETAILS

DEMOLITION FLOOR PLAN FIRST FLOOR PLAN

LARGE SCALE PLANS AND DETAILS A2.3 LARGE SCALE PLAN DETAILS A2.4 OSL FLOOR PLAN

EXTERIOR ELEVATIONS BUILDING SECTIONS

A5.1 WALL SECTIONS A6 1 DOOR & ROOM FINISH SCHEDULES AND DETAILS

DOOR & MISCELLANEOUS DETAILS A7.1 INTERIOR ELEVATIONS A7.2 INTERIOR DETAILS

ROOF PLAN - NOTES ROOF DETAILS

CEILING PLAN - DETIALS A10.1 PARTITION DETAILS A10.2 DETAILS

PARTIAL ROOF FRAMING PLAN

MECHANICAL LEGEND & NOTES MECHANICAL SCHEDULES FIRST FLOOR DEMO PLAN - MECHANICAL ROOF DEMO PLAN - MECHANICAL

FIRST FLOOR PLAN — PLUMBING FIRST FLOOR PLAN - HVAC ROOF PLAN - HVAC

ELECTRICAL LEGEND, ABBREVIATIONS & GENERAL NOTES

ELECTRICAL SCHEDULES ELECTRICAL SCHEDULES E1.0 ELECTRICAL SITE PLAN ED1.1 ELECTRICAL DEMOLITION PLAN

E2.0 ELECTRICAL LIGHTING PLAN ELECTRICAL POWER PLAN E4.0 ELECTRICAL SYSTEMS PLAN E5.0 ELECTRICAL ONE-LINE DIAGRAM

ELECTRICAL DETAILS

SCOPE OF WORK

THE SCOPE OF WORK INCLUDES, BUT IS NOT LIMITED TO THE FOLLOWING:

SELECTIVE DEMOLITION OF INTERIOR OF REMAINING BUILDING INCLUDING INTERIOR PARTITIONS, CEILINGS, FLOOR, MECHANICAL AND ELECTRICAL ETC..

EXPAND EXISTING CARRIER ANNEX INTO NORTH END OF BUILDING, ADD LOCKER ROOMS, NEW LAVATORIES AND ACCESSORIES IN EXISTING TOILET ROOMS. RECONFIGURE EXISTING MAIL VESTIBULE AND CONSTRUCT NEW CARRIER VESTIBULE AT EXISTING LOADING DOCK AREA, INSTALL NEW DOCK DOORS AND SCISSORS LIFTS, ADD DOORS, ETC. EXISTING INSULATION SITS ON TOP OF EXISTING CEILINGS. FOR A SIGNIFICANT PORTION OF THE WORK THE CEILINGS AND INSULATION ARE BEING REMOVED, NEW DESIGN SHOWS NEW INSULATION SELF SUPPORTED ABOVE NEW CEILINGS.

SITE WORK INCLUDES CONSTRUCTION OF LOADING DOCK, CARRIER AND EMPLOYEE PARKING AREAS, STORM DRAINAGE, FENCING, SITE LIGHTING, NEW AND OVERLAY OF EXISTING ASPHALT, PARKING STRIPING,

2 EXISTING DOUBLE ACTION VESTIBULE DOORS AND EXISTING AND MAY BE REUSED IN NEW CONFIGURATION SHOWN.

PLUMBING WORK: REPLACE LAVATORIES IN TOILET ROOMS. REMOVE HAIR WASH SINK FOR BREAK ROOM, DEMOLISH ONE TOILET ROOM AND CAP ALL PLUMBING.

MECHANICAL SCOPE OF WORK: REPLACE ROOF TOP EQUIPMENT WHERE SHOWN, MAKE MODIFICATIONS TO DUCTWORK AS REQUIRED FOR NEW CEILING CONFIGURATIONS, INSTALL TEMPERATURE CONTROLS.

FIRE ALARM: RECONFIGURE EXISTING SYSTEMS AND INSTALLATION OF NEW INCLUDING PERMITTING FROM CITY OF SEATTLE FIRE MARSHAL.

ELECTRICAL SCOPE OF WORK: PROVIDE ADDITIONAL POWER AND DATA AS SHOWN AS WELL AS REMOVAL OF DEVICES AND WIRING WHERE EXISTING WALLS AND CEILINGS ARE BEING RECONFIGURED. CCTV: MODIFY AND EXPAND EXISTING CCTV SYSTEM AS SHOWN.



VICINITY MAP




REGISTERED ARCHITECT STEVEN A. BARNES

STATE OF WASHINGTON


 $\overline{}$










ANNE










INLET PROTECTION NOTES: 1. FILTERS SHALL BE REMOVED AND CLEANED OR REPLACED AFTER EACH STORM EVENT AND ON A WEEKLY BASIS.





CONSTRUCTION STORMWATER CONTROL (CSC) GENERAL NOTES

- 1. A FIRST GROUND DISTURBANCE INSPECTION IS REQUIRED PRIOR TO START OF WORK ON ALL SITES WITH LAND DISTURBING ACTIVITY.
- 2. SCHEDULE A FIRST GROUND DISTURBANCE INSPECTION FOR AN ISSUED BUILDING PERMIT AT 206-684-8900 OR ONLINE AT WWW.SEATTLE.GOV/DPD/PERMITS/INSPECTIONS/
- 3. THE APPLICANT SHALL DESIGNATE AN EROSION AND SEDIMENT CONTROL (ESC) SUPERVISOR WHO SHALL BE RESPONSIBLE FOR THE INSTALLATION AND MAINTENANCE OF EROSION AND SEDIMENT CONTROL BEST MANAGEMENT PRACTICES (BMPS). FOR LARGE CONSTRUCTION PROJECTS, THE ESC SUPERVISOR SHOULD BE A CERTIFIED EROSION AND SEDIMENT CONTROL LEAD (CESCL). PROVIDE THE NAME AND PHONE NUMBER OF THE ESC SUPERVISOR TO THE SITE INSPECTOR AT THE FIRST GROUND DISTURBANCE INSPECTION.
- 4. BMPS SHALL BE INSTALLED PRIOR TO STARTING CONSTRUCTION TO ENSURE SEDIMENT-LADEN WATER DOES NOT LEAVE THE PROJECT SITE OR ENTER ROADSIDE DITCHES, STORM DRAINS, SURFACE WATERS, OR WETLANDS.
- 5. THE BMPS INCLUDED IN THIS PLAN ARE THE MINIMUM REQUIREMENTS FOR ANTICIPATED SITE CONDITIONS. THE APPLICANT IS RESPONSIBLE FOR ENSURING THAT BMPS ARE MODIFIED AS NEEDED FOR UNEXPECTED STORM EVENTS OR OTHER UNFORESEEN CIRCUMSTANCES, AND TO ACCOUNT FOR CHANGING SITE CONDITIONS.
- 6. ANY AREAS OF DISTURBED SOIL THAT WILL NOT BE WORKED FOR TWO CONSECUTIVE DAYS DURING THE WET SEASON (OCT 1 TO APRIL 30) OR SEVEN DAYS DURING THE DRY SEASON (MAY 1 TO SEPT 30) SHALL BE IMMEDIATELY STABILIZED WITH APPROVED BMPS METHODS (E.G. STRAW, MULCH, PLASTIC COVERING, COLD MIX, ETC.)
- 7. GRADING AND/OR SOIL DISTURBING ACTIVITIES MAY BE LIMITED OR PROHIBITED FOR CERTAIN SITES SUBJECT TO ECA STANDARDS (I.E. ECA STEEP SLOPES, LANDSLIDE PRONE AREAS, ETC.) BETWEEN OCTOBER 31ST AND APRIL 1ST. IF NOTED IN THE GEOTECHNICAL SPECIAL INSPECTIONS REQUIREMENTS, A GRADING SEASON EXTENSION LETTER (GSEL) ISSUED BY SDCI IS REQUIRED FOR ALL GRADING AND/OR SOIL DISTURBING ACTIVITIES DURING THIS PERIOD. THE GEOTECHNICAL SPECIAL INSPECTOR MUST SUBMIT ELECTRONIC APPLICATIONS FOR A GSEL USING THE SDCI PROJECT PORTAL. ALLOW FOUR TO SIX WEEKS FOR PROCESSING. FAILURE TO OBTAIN THE GSEL PRIOR TO OCTOBER 31 MAY
- 8. CITY STREETS AND SIDEWALKS SHALL BE KEPT CLEAN AT ALL TIMES. NO MATERIAL SHALL BE STORED ON CITY STREETS OR SIDEWALKS WITHOUT A STREET USE PERMIT FROM THE SEATTLE DEPARTMENT OF TRANSPORTATION
- 9. POLLUTION CONTROL MEASURES SHALL BE FOLLOWED TO ENSURE THAT NO LIQUID PRODUCTS OR CONTAMINATED WATER ENTERS ANY STORM DRAINAGE FACILITIES OR OTHERWISE LEAVES THE PROJECT SITE. ANY HAZARDOUS MATERIALS OR LIQUID PRODUCTS THAT HAVE THE POTENTIAL TO POLLUTE RUNOFF SHALL BE STORED AND DISPOSED
- 10. ENSURE THAT WASHOUT FROM CONCRETE TRUCKS IS PERFORMED OFF-SITE OR IN DESIGNATED CONCRETE WASHOUT AREAS ONLY. DO NOT WASH OUT CONCRETE TRUCKS ONTO THE GROUND, OR TO STORM DRAINS OR OPEN DITCHES. DO NOT DUMP EXCESS CONCRETE ONSITE, EXCEPT IN DESIGNATED CONCRETE WASHOUT AREAS.
- 11. ALL AREAS OF DISTURBED SOIL SHALL BE FULLY STABILIZED WITH THE APPROPRIATE SOIL AMENDMENT AND COVER MEASURES AT COMPLETION OF THE PROJECT. TYPICAL COVER MEASURES INCLUDE LANDSCAPING OR HYDROSEED

CONSTRUCTION STORMWATER CONTROL (CSC) PLAN REQUIREMENTS

- THE BMPS SHOWN ON THE <u>ESC PLAN (SHEET C1.2)</u> ARE THE MINIMUM REQUIRED. ADDITIONAL BMPS ARE REQUIRED WHEN MINIMUM CONTROLS ARE NOT SUFFICIENT TO PREVENT EROSION OR TRANSPORT OF SEDIMENT OR OTHER POLLUTANTS FROM THE SITE.
- MARK CLEARING LIMITS - DELINEATE ENVIRONMENTALLY CRITICAL AREAS
- RETAIN TOP LAYER AND NATIVE VEGETATION - ESTABLISH CONSTRUCTION ACCESS
- PROTECT DOWNSTREAM PROPERTIES AND RECEIVING WATERS - PREVENT EROSION AND SEDIMENT TRANSPORT FROM THE SITE
- STABILIZE SOILS - PROTECT SLOPES
- PROTECT STORM DRAINS STABILIZE CHANNEL AND OUTLETS
- CONTROL POLLUTANTS CONTROL DEWATERING - MAINTAIN AND INSPECT BMPs
- EXECUTE CONSTRUCTION STORMWATER CONTROL PLAN
- MINIMIZE OPEN TRENCHES - PHASE THE PROJECT
- INSTALL PERMANENT FLOW CONTROL AND WATER QUALITY FACILITIES - PROTECT STORMWATER BMPs PRIOR TO, DURING, AND AFTER CONSTRUCTION

COMPLETE CONSTRUCTION STORMWATER CONTROL BMP DETAILS AND REQUIREMENTS ARE LOCATED IN DIRECTOR'S RULE DPD DR 21-2015, CHAPTER 4, VOLUME 2: CONSTRUCTION STORMWATER CONTROL, OF THE SEATTLE STORMWATER MANUAL. SHOW ALL BMPS ON THIS PLAN SHEET THAT WILL BE USED TO ACHIEVE THE REQUIREMENTS ABOVE.

TEMPORARY EROSION CONTROL SEED MIX

* APPLY AT A RATE OF 120 LBS / AC. * APPLY WITH MULCH OR TOPSOIL AS NECESSARY

CHEWINGS OR ANNUAL BLUE GRASS Festuca rubra var. commutata or Poa anna	<u>%WT</u>	%PURITY 98	%GERMINATION 90
PERENNIAL RYE Lolium perenne	50	98	90
REDTOP OR COLONIAL BENTGRASS Agrostis alba or Agrostis tenuis	5	92	85
WHITE DUTCH CLOVER Trifolium repens	5	98	90

FILTER FENCE TREE & VEGETATION PROTECTION - FILTER FABRIC MATERIAL 60" WIDE BOLLS. USE STAPLES OR WIRE RINGS TO ATTACH FABRIC TO WIRE MIRAFI 700X OR PRE-APPROVED EQUAL 1. CHAIN LINK, WIRE MESH, OR SIMILAR OPEN — 2" X 2" X 14ga WIRE FABRIC OR -METAL FENCE POSTS RIGID MATERIAL (NO PLYWOOD) EQUIV. (OPTIONAL-PER SITE CONDITION) 2. MUST BE INSTALLED PRIOR TO DEMOLITION OR GROUND DISTURBANCE 3. KEPT IN PLACE FOR THE DURATION OF BURY BOTTOM OF FILTER CONSTRUCTION MATERIAL IN 8" X 12" TRENCH 4. NO SOIL DISTURBANCE OR ACTIVITY ALLOWED WITHIN FENCED AREA: MATERIAL STORAGE/STOCKPILING, PARKING, EXCAVATION, DUMPING, OR WASHING 5. MODIFICATIONS OF THESE REQUIREMENTS BY APPROVAL OF SDCI PLANNER ONLY 6. IF ROOTS GREATER THAN 2 INCH FOUND OUTSIDE OF FENCING, PROTECT BY HAND MAXIMUM EXCAVATION AND, IF NECESSARY, CUT CLEANLY AND KEEP MOIST 7. USE 3 INCHES OR DEEPER WOOD CHIP MULCH OUTSIDE FENCED AREAS TO FILTER FABRIC MATERIAL PROTECT FEEDER ROOTS BACKFILL WITH WASHED VEGETATION PROTECTION GRAVEL BACKFILL IN TRENCH AND ON BOTH SIDES OF 1. ORANGE MESH OR SIMILAR OPEN MATERIAL FENCE FABRIC ON THE 2. MINIMIZE CONSTRUCTION ZONE SURFACE. NATIVE BACKFIL 3. PROTECT VEGETATION OUTSIDE MAY BE USED IF APPROVED TREE & VEGETATION FENCING AROUND ENTIRE DRIP LINE ON PERMIT SITE. ALTERNATIVE TREE PROTECTION, IF APPROVED CONSTRUCTION ZONE WITH FENCING AS 4. USE 3 INCHES OR DEEPER WOOD CHIP BY SDCI, AS SHOWN ON SITE PLAN MULCH OUTSIDE FENCED AREAS TO PROTECT FEEDER ROOTS NOTE: ANGLE SILT FENCE BACK UP THE SLOPE AT THE END OF RUN. PROTECTION INFORMATION: SYMBOL: O O O O STOCKPILE AND EXPOSED SLOPE COVERING BURY SHEETING IN 4"x6" TRENCH A MIN. OF 8 FT. SETBACK FROM TOP OF 6 MIL (MIN) CLEAR PLASTIC ANCHOR WEIGHTS WITH ANCHOR WEIGHTS WITH SLOPE, BACKFILL WITH - STAKES WASHED ROCK WATTLE CONVEY RUNOFF TO PROVIDE ENERGY APPROVED LOCATION DISSIPATION AT TOF WHEN NEEDED -TOE IN SHEETING IN 4"x6" TRENCH A MIN. OF 3 FT. SETBACK FROM BOTTOM OF SLOPE. BACKFILL WITH WASHED CONVEY RUNOFF TO APPROVED LOCATION STOCKPILES CONVEY RUNOFF TO APPROVED LOCATION <u>SLOPES</u> SYMBOL:



AT THE END OF PROJECT. ALL AREAS DISTURBED AND NOT COVERED WITH A HARD SURFACE MUST BE AMENDED PER THE SOIL AMENDMENT DETAIL BELOW AND PROBE TO 12-INCHES AT THE SITE FINAL INSPECTION.

> LABEL ALL AREAS DISTURBED AND NOT COVERED WITH A HARD SURFACE WITHIN THE SITE AS ONE OF THE FOLLOWING: SA (SOIL AMENDMENT AREA) or ND (NON-DISTURBED AREA). SEE DEFINITIONS BELOW. DO NOT REFERENCE AN ALTERNATE PLAN SHEET.

> AN ESTIMATE OF THE VOLUME OF COMPOST REQUIRED IS AUTOMATICALLY CALCULATED ON THE SITE AND DRAINAGE CONTROL SUMMARY SHEET REQUIRED ON THE DRAINAGE AND WASTEWATER CONTROL PLAN (DWC PLAN). THE ACTUAL VOLUME OF COMPOST REQUIRED WILL BE DETERMINED IN THE FIELD.


DEFINITIONS:

NON-DISTURBED AREA (ND): VEGETATED AREAS THAT WILL NOT BE SUBJECT TO LAND DISTURBING ACTIVITY (SEE D) DO NOT REQUIRE SOIL AMENDMENT IF THEY ARE FENCED AND CONTINUOUSLY PROTECTED THROUGHOUT CONSTRUCTION. THE FENCING MUST BE IN PLACE AT THE FIRST GROUND DISTURBANCE INSPECTION. THIS WILL BE MONITORED BY THE DPD SITE INSPECTOR. NO DISTURBANCE, INCLUDING VEHICLE TRAFFIC OR MATERIAL STORAGE, IS ALLOWED IN THESE AREAS UNTIL FINAL INSPECTION. LABEL THESE AREAS AS (ND) IN THE PLAN

SOIL AMENDMENT AREA (SA): VEGETATED OR COMPOST AREAS (TURF AND LANDSCAPE) MUST BE AMENDED PER THE SOIL AMENDMENT DETAIL AND THE SUBSOIL MUST BE LOOSENED SO IT WILL PROBE TO A DEPTH OF 12 INCHES PRIOR TO SITE FINAL INSPECTION. THIS INCLUDES AREAS IMPACTED BY CLEARING AND GRADING, STOCKPILING, SITE ACCESS, PATHWAYS AND MATERIALS OR EQUIPMENT STORAGE. LABEL THESE AREAS AS (SA) IN THE PLAN VIEW.

ESTIMATED COMPOST REQUIRED FOR SOIL AMENDMENT

***ONLY COMPLETE THE FOLLOWING CALCULATION IF A DRAINAGE AND WASTEWATER CONTROL PLAN (DWC PLAN) IS



(ND) NON-DISTURBED AREA (SOIL AMENDMENT NOT REQUIRED)

CONSTRUCTION STORMWATER CONTROL & POST CONSTRUCTION SOIL MANAGEMENT DETAILS

NOTE: THIS PLAN IDENTIFIES THE MINIMUM MEASURES REQUIRED; ADDITIONAL MEASURES MAY BE REQUIRED BASED ON CONSTRUCTION METHODS AND ACTUAL AREA OF DISTURBANCE.


9

200 SEWER-DRAINAGE APPURTENANCES

STORM S	TRUCTURE / CLEAN	OUT SCHEE	DULE
CB/CO	TYPE	RIM	ΙE
1	SDMH, TY. 204A	128.00	121.80 (8"W) 121.80 (8"E)
2	CB, TY. 241a BIORETENTION CB	126.25	122.17 (6"W) 122.00 (8"E)
3	CLEANOUT	126.25	122.29 (6")
•			

STORM PIPE SCHEDULE PIPE DIA / TYPE LENGTH (FT) SLOPE A 8" PVC,SCH40 15 (END/END) 1.33% B 8" PVC,SCH40 13 1.54% C 6" PVC,SCH40 12 1.00% SLOTTED PIPE D 8" PVC,SCH40 24 1% MIN.				
A 8" PVC,SCH40 15 (END/END) 1.33% B 8" PVC,SCH40 13 1.54% C 6" PVC,SCH40 12 1.00% SLOTTED PIPE D 8" PVC,SCH40 24 1% MIN.	STORM	PIPE SCHEDULE		
B 8" PVC,SCH40 13 1.54% C 6" PVC,SCH40 12 1.00% SLOTTED PIPE D 8" PVC,SCH40 24 1% MIN.	PIPE	DIA / TYPE	LENGTH (FT)	SLOPE
C 6" PVC,SCH40 12 1.00% SLOTTED PIPE D 8" PVC,SCH40 24 1% MIN.	А	8" PVC,SCH40	15 (END/END)	1.33%
SLOTTED PIPE D 8" PVC,SCH40 24 1% MIN.	В	8" PVC,SCH40	13	1.54%
D 8" PVC,SCH40 24 1% MIN.	С	6" PVC,SCH40	12	1.00%
		SLOTTED PIPE		
1 A' MINI COMED DELOM MALL	D	,		1% MIN.
I MIN. COVER BELOW WALL		1' MIN. COVER BELOW	WALL	
E 6" PVC,SCH40 20 3.00%	Е	6" PVC,SCH40	20	3.00%

STORM	PIPE SCHEDULE DIA / TYPE	LENGTH (FT)	SLOPE
А	8" PVC,SCH40	15 (END/END)	1.33%
В	8" PVC,SCH40	13	1.54%
С	6" PVC,SCH40 SLOTTED PIPE	12	1.00%
D	8" PVC,SCH40 1' MIN. COVER BELOW W	24 ALL	1% MIN.
Е	6" PVC,SCH40	20	3.00%



BIORETENTION CELL - PLAN

LANDSCAPING PER 'L' SHEETS

-OUTFALL PAD (TYP)

2"-4" QUARRY SPALLS


/ DRAIN EX. PARKING AREA

1 inch = 5 ft.


1' THICK

-CONC. CURB









2017 Edition City of Seattle Standard Plans for Municipal Construction

BIORETENTION SOIL

THE MINIMUM REQUIREMENTS ASSOCIATED WITH BIORETENTION SOIL DESIGN INCLUDE: THE BIORETENTION SOIL SHALL MEET CITY OF SEATTLE STANDARD SPECIFICATION 7-21. SOIL SHALL BE A WELL-BLENDED MIXTURE OF 2 PARTS FINE COMPOST (APPROXIMATELY 35 TO 40 PERCENT) BY VOLUME AND 3 PARTS MINERAL AGGREGATE (APPROXIMATELY 60 TO 65 PERCENT) BY VOLUME. THE MIXTURE SHALL BE WELL BLENDED TO PRODUCE A HOMOGENEOUS MIX, AND HAVE AN ORGANIC MATTER CONTENT OF 4 TO 8 PERCENT DETERMINED USING THE LOSS ON IGNITION METHOD. MATERIALS SHALL MEET THE CRITERIA

FINE COMPOST FOR BIORETENTION SOIL SHALL MEET THE CRITERIA BELOW: 1. GRADATION. FINE COMPOST SHALL MEET THE FOLLOWING SIZE GRADATIONS BY DRY WEIGHT WHEN TESTED IN ACCORDANCE WITH THE U.S. COMPOSTING COUNCIL TESTING METHODS FOR THE EXAMINATION OF COMPOST AND COMPOSTING (TMECC) TEST METHOD 02.02-B, SAMPLE SIEVING FOR AGGREGATE SIZE CLASSIFICATION:


		PERCENT	PASSI
SII	EVE SIZE	MINIMUM	MAX
	2"	100%	
	1"	99%	10
	5/8 "	90%	10
	1/4"	75%	10


- 2. PH. THE PH SHALL BE BETWEEN 6.0 AND 8.5 WHEN TESTED IN ACCORDANCE WITH
- TMECC 04.11-A; "1:5 SLURRY PH." 3. PHYSICAL CONTAMINANTS. MANUFACTURED INERT MATERIAL (CONCRETE, CERAMICS, METAL, ETC.) SHALL BE LESS THAN 1.0 PERCENT BY WEIGHT AS DETERMINED BY TMECC 03.08-A "PERCENT DRY WEIGHT BASIS." FILM
- PLASTICS SHALL BE 0.1 PERCENT OR LESS, BY DRY 4. ORGANIC CONTENT. MINIMUM ORGANIC MATTER CONTENT SHALL BE 40 PERCENT BY DRY WEIGHT BASIS AS DETERMINED BY TMECC 05.07-A; LOSS-ON-IGNITION ORGANIC
- MATTER METHOD. 5. SALINITY. SOLUBLE SALT CONTENTS SHALL BE LESS THAN 5.0 MMHOS/CM TESTED IN ACCORDANCE WITH TMECC 04.10-A: "1:5 SLURRY METHOD, MASS BASIS."
- 6. MATURITY. MATURITY SHALL BE GREATER THAN 80 PERCENT IN ACCORDANCE WITH TMECC 05.05-A; "GERMINATION AND VIGOR." THE ENGINEER MAY ALSO EVALUATE COMPOST FOR MATURITY USING THE SOLVITA COMPOST MATURITY TEST AT TIME OF DELIVERY. FINE COMPOST SHALL SCORE A NUMBER 6 OR ABOVE ON THE SOLVITA COMPOST MATURITY TEST. COARSE COMPOST SHALL SCORE A 5 OR ABOVE ON THE SOLVITA COMPOST MATURITY TEST.
- 7. STABILITY. STABILITY SHALL BE 7 OR BELOW IN ACCORDANCE WITH TMECC 05.08-B; "CARBON DIOXIDE EVOLUTION RATE."
- 8. FEEDSTOCKS. THE COMPOST PRODUCT SHALL CONTAIN A MINIMUM OF 65 PERCENT BY VOLUME FROM RECYCLED PLANT WASTE AS DEFINED IN WAC 173-350-100 AS "YARD WASTE," "CROP RESIDUES," AND "BULKING AGENTS." A MAXIMUM OF 35 PERCENT BY VOLUME OF "POSTCONSUMERFOOD WASTE" AS DEFINED IN WAC 173-350-100 MAY BE SUBSTITUTED FOR RECYCLED PLANT WASTE. A MINIMUM OF 10 PERCENT FOOD WASTE IN COMPOST IS REQUIRED. THE ENGINEER MAY APPROVE COMPOST PRODUCTS CONTAINING UP TO 35 PERCENT BIOSOLIDS OR MANURE FEEDSTOCKS FOR SPECIFIC PROJECTS OR SOIL BLENDS, BUT THESE FEEDSTOCKS ARE NOT ALLOWED UNLESS
- SPECIFIED, AND NOT ALLOWED IN COMPOST USED FOR BIORETENTION SOILS. 9. C:N. FINE COMPOST SHALL HAVE A CARBON TO NITROGEN RATIO OF LESS THAN 25:1 AS DETERMINED USING TMECC 04.01 "TOTAL CARBON" AND TMECC 04.02D "TOTAL KJELDHAL NITROGEN." THE ENGINEER MAY SPECIFY A C:N RATIO UP TO 35:1 FOR PROJECTS WHERE THE PLANTS SELECTED ARE ENTIRELY PUGET SOUND NATIVE SPECIES. COMPOST MAY BE MIXED WITH FIR OR HEMLOCK BARK MEETING REQUIREMENTS OF 9-14.4(3) TO RAISE THE C:N RATIO ABOVE 25:1. COARSE COMPOST SHALL HAVE A CARBON TO NITROGEN RATIO BETWEEN 20:1 AND 45:1.


MINERAL AGGREGATE FOR BIORETENTION SOIL SHALL BE ANALYZED BY AN ACCREDITED LAB USING THE SIEVE SIZES NOTED BELOW, AND SHALL MEET THE FOLLOWING GRADATION:

SIEVE SIZE	PERCENT PASS
3/8"SQUARE	100
ÚS. NO. 4	60 - 100
US. NO. 10	40 - 100
US. NO. 40	15 - 50
US. NO. 200	2 - 5


FOR FACILITIES WITHOUT UNDERDRAINS, BIORETENTION SOIL DEPTH SHALL BE A MINIMUM DEPTH OF 12 INCHES TO MEET ON-SITE STORMWATER MANAGEMENT AND FLOW CONTROL REQUIREMENTS, AND 18 INCHES TO MEET WATER QUALITY TREATMENT REQUIREMENTS. FOR FACILITIES WITH UNDERDRAINS, THE BIORETENTION SOIL SHALL HAVE A MINIMUM DEPTH OF 18 INCHES.








2017 Edition City of Seattle Standard Plans for Municipal Construction



2017 Edition City of Seattle Standard Plans for Municipal Construction



2017 Edition City of Seattle Standard Plans for Municipal Construction

0.36

40' MAX

-MAINTENANCE HOLE FRAME & COVER SEE STD PLAN NO 230

4'-0" TO 2'-0" PRECAST CONCENTRIC CONE SECTION

MH LADDER SEE STD PLANS NO 2320 & 232b

PRECAST BASE

TYPE 9 MINERAL AGGREGATE

W/ PORTLAND CEMENT FOR PRECAST BASE OR PRECAST

BASE WITH INTEGRAL RISER

-LOCATION OF MH

PLAN VIEW

(TOP REMOVED)

OPENING

SECTION B-E

-REINFORCING -

HANDHOLDS SEE STD

LEVELING BRICKS OR CONCRETE COLLAR

MORTAR FILLET -

UNDISTURBED EARTH OR TYPE

2 MINERAL AGGREGATE 4" MIN THICKNESS FOR CAST-IN-PLACE BASE SECTION

REF STD SPEC SEC 7-05

PLANS NO 232a & 232b-

CAST-IN-PLACE BASE

LADDER FOR TYPE A MAINTENANCE HOLE.

EXTENDED &'S
OF SEWER PIPES
INTERSECT AT &

0.25

NOTES:

1. MATERIALS: CONCRETE—CLASS 4000;
REINFORCING STEEL—ASTM A615 GRADE
60 MIN; CHANNEL AND SHELF MATERIAL
— CONCRETE CLASS 3000.

2. PRECAST MAINTENANCE HOLE
COMPONENTS SHALL CONFORM TO ASTM
C 478. JOINTS BETWEEN PRECAST
COMPONENTS MUST BE RUBBER
GASKETED CONFORMING TO ASTM C 443.
3. MINIMUM REQUIRED SOIL BEARING =

MINIMUM REQUIRED SOIL BEARING =

MAX HOLE SIZE MUST BE OD OF PIPE PLUS 5 IN. MIN HOLE SIZE MUST BE OD OF PIPE PLUS 3 IN. MIN CLEAR


DISTANCE BETWEEN HOLES IS 8 IN.

3,000 LBS/SQ FT

ANNEX

CARRIER ANNEX
NEAU STREET
118





2017 Edition City of Seattle Standard Plans for Municipal Construction

2017 Edition City of Seattle Standard Plans for Municipal Construction

NOT TO SCALE

200 SEWER-DRAINAGE APPURTENANCES

CLASS B BEDDING

CLASS C BEDDING

CLASS D BEDDING

City of Seattle

REF STD SPEC SEC 2-10.2, 7-11, 7-17, 9-03.16

STANDARD PLAN NO 285

METALLIC PIPE: STORM OR SEWER

XCXCXCXCXCXCXCXCXCXCXCXCXCXC

SAND BEDDING AT TRENCH CROSSING OF METAL PIPE AT METALLIC PIPE CROSSING OF FLUIDIZED

THERMAL BACKFILL OR CDF CONDUIT CROSSINGS

STD SPEC 2-10.2(1)

SUITABLE BACKFILL

MINERAL AGGREGATE PER STD SPEC 9-03.16
TYPE 9 FOR DUCTILE IRON WHEN APPLICABLE
OR CONCRETE PIPE TYPE 22 FOR VITRIFIED
CLAY AND FLEXIBLE PIPE

SELECTED NATIVE MATERIAL PER

FLUIDIZED THERMAL BACKFILL PER SCL MATERIAL STD 7150.00 OR CDF (SEE CONTRACT DRAWINGS)

PIPE BEDDING SEWER/STORM DRAIN

MINERAL AGGREGATE PER STD SPEC 9-03.16, TYPE 6 OR TYPE 7

NOTES:

1. FOR TRENCH WIDTH SEE STD PLAN NO 284

2. A=4"WHEN ID IS LESS THAN 2"-6", A=6"WHEN ID IS 2"-6"OR MORE.


3. UNIFORMLY SUPPORT PIPE BARREL. EXCAVATE HOLES FOR BELLS AND COUPLING.

REV DATE: MAY 201

FLUIDIZED
THERMAL
BACKFILL OR
CDF

DUCT BANK CROSSING

COLUMBIA CARRIER ANNEX 3613 SOUTH JUNEAU STREET SEATTLE, WA 98118



PLANT SCHEDULE

SHRUBS	CONTINUE NAME				
SYMBOL	SCIENTIFIC NAME COMMON NAME	QUANTITY	SIZE (MIN.)	SPACING (MAX.)	NOTES
\bigcirc	 CORNUS "HALO" VARIEGATED RED TWIG DOGWOOD 	3	2 GALLON	AS SHOWN	FULL, WELL SHAPED
⊗ —	 MISCANTHUS 'ADIAGO' ADIAGO MAIDEN GRASS 	10	1 GALLON	AS SHOWN	MULTI- STEM, FULL
(PP)	- PINUS MUGHO 'PUMILIO' PUMILIO MUGHO PINE	8	2 GALLON	AS SHOWN	NICE FOLIAGE, MULTI STEMS
	– ROSA NUTKANA NOOTKA ROSE	5	1 GALLON	AS SHOWN	BUSHY, FULL
⊕ ———	– SPIEA 'TOR' BIRCHLEAF SPIREA	5	2 GALLON	AS SHOWN	FULL, BUSHY, WELL SHAPED
(a)	 WEGELIA 'WINE & ROSES' CARDINAL FLOWER 	6	2 GALLON	AS SHOWN	FULL, NICE SHAPE, UNIFORM

GROUNDCOVER

MBOL	SCIENTIFIC NAME COMMON NAME	QUANTITY	SIZE (MIN.)	SPACING (MAX.)	NOTES	
	CORNUS KELSEYII DWARF RED TWIG DOGWOOD	115 sf	1 GALLON	24 " TRIANGULAR	FULL, MULTI STEMMED, HEALTHY	
	MAHONI REPENS LOW GROWING OREGON GRAPE	175 sf	1 GALLON	24" TRIANGULAR	FULL, NICE FOLIAGE	
	RAIN GRADEN GRASSES: CAREX OBNUPTA, JUNCUS 'BLUE ELK' SCIRPUS MICROCARPUS	90 sf	1 GALLON	24" TRIANGULAR	HEALTHY FOLIAGE, WELL ROOTED	
	NOTF:					

- GROUNDCOVER TO BE PLANTED TO ACHIEVE FULL COVERAGE WITHIN THREE YEARS. CONTRACTOR TO DETERMINE QUANTITY TO ACHIEVE SPACING SPECIFIED. - GROUNDCOVER IS NOT REQUIRED UNDER CANOPY OF SHRUBS OR WITHIN TREE WELLS.

EXISTING PLANTING BED AREAS TO REMAIN REMOVE ANY INVASIVE SPECIES.

LANDSCAPE NOTES GENERAL:

* UTILITY LOCATION: DETERMINE ALL ABOVE GRADE AND UNDERGROUND UTILITIES BEFORE COMMENCING WORK. ALL WORK TO BE COMPLETED TO AVOID ANY DAMAGE. THIS IS THE RESPONSIBILITY OF THE CONTRACTOR. ANY UTILITIES SHOWN ON PLAN ARE APPROXIMATE ONLY AND NOT VERIFIED.

- 1. ALL EXISTING VEGETATION AREAS TO RECEIVE NEW LANDSCAPE SHALL BE CLEARED AND GRUBBED FROM THE SITE PRIOR TO COMMENCEMENT OF LANDSCAPE WORK. 2. SUBGRADES FOR ALL PLANTING BED AREAS SHALL BE 6" MINIMUM BELOW FINISH
- ELEVATION. ALL PLANTING BEDS TO HAVE POSITIVE DRAINAGE. MINIMUM 3%. 3. ALL PLANTING BEDS TO BE NON-COMPACTED TO A DEPTH OF 18" PRIOR TO
- 4. EXISTING CLAY OR SANDY SOILS SHALL BE AUGMENTED WITH ORGANIC SUPPLEMENTS. SOIL ANALYSIS MAY BE REQUIRED.
- AFTER APPROVED COMPLETION.

5. CONTRACTOR SHALL GUARANTEE PLANTS AND GRASS FOR A MINIMUM OF ONE YEAR

6. IMMEDIATELY NOTIFY OWNER REPRESENTATIVE OF ANY ADVERSE CONDITIONS OR CONFLICTS WHICH MAY AFFECT HEALTH OF PLANT MATERIAL.

CONTAINER SHRUB PLANTING DETAIL

L1.1 SCALE: N.T.S.

PLANTING BEDS:

- 1. PLANTING BEDS TO HAVE A MINIMUM OF 12" (MORE TO MEET TOP OF ANY PAVEMENT OR CURB) OF APPROVED THREE WAY TOPSOIL. BEDS TO BE NONCOMPACTED TO A DEPTH OF 18". PLANTING BEDS TO HAVE MORE SOIL IF NECESSARY TO BE FLUSH WITH CURB, SIDEWALK OR OTHER PAVED SURFACE. ALL PLANTING BEDS TO HAVE POSITIVE DRAINAGE. FOR AREAS WITH EXISTING SOILS, AMMEND SOIL PER POST CONSTRUCTION
- MANAGEMENT PLAN: REFER TO C1.5 ON CIVIL PLANS. * NO DEBRI, RIP RAP, OR PAVING BASE OR OTHER MATERIALS THAT ARE NOT SOIL ARE NOT TO BE IN PLANTER BEDS. IF ADDITIONAL MATERIAL IS TO BE REMOVED, CONTRACTOR SHALL INSTALL ADDITIONAL SOIL TO ENSURE THAT FINISH GRADE IS FLUSH WITH HARDSCAPE. SOIL DEPTH IS TO BE A MINIMUM OF 24" VIABLE PLANT GROWTH MATERIAL.
- 2. CONTRACTOR TO VERIFY PLANT QUANTITIES AND SQUARE FOOTAGE. NOTIFY TERRAFORMA DESIGN GROUP IF THERE IS A DISCREPANCY.
- 3. ALL PLANT MATERIAL TO BE WELL BRANCHED, FREE FROM DISEASE OR PEST, AND HAVE A WELL DEVELOPED ROOT SYSTEM. ALL MATERIAL TO MEET AMERICAN ASSOCIATION OF NURSERYMEN STANDARDS.
- 4. FERTILIZE ALL PLANT MATERIAL WITH SLOW RELEASE FERTILIZER PER MANUFACTURER'S RATES.(NOT INCLUDING RAIN GARDEN AREA) 5. PLANT MATERIAL PLANTED TO BE SAME AS OR NO MORE THAN 1" HIGHER THAN CURRENT GROWTH RATE AT FINISH GRADE.
- 6. WATER PLANTS THOROUGHLY DURING PLANTING AND IMMEDIATELY FOLLOWING. WATER HEAVILY AT FIRST , 3 TIMES PER WEEK, AND LESS ONCE ESTABLISHED. 7. ORGANIC MEDIUM MULCH TO BE A MINIMUM OF 3" DEPTH COMACTED IN ALL

RAIN GARDEN:

- 1. INSTALL RAIN GARDEN PER CIVIL ENGINEERING DRAWINGS. SEE DETAIL OF NON-INFILTRATING BIORETENTION AND OTHER INFORMATION. 2. FOLLOW ALL CIVIL ENGINEERING REQUIREMENTS, INCLUDING BUT NOT LIMITED TO : SOIL DEPTH, TYPE, MULCH, DRAINAGE, AND INSTALLATION PER CIVIL ENGINEER.
- 3. INSTALL COMPOST AND ARBORIST WOOD CHIPS AS MULCH PER ENGINEER DRAWINGS. 4. DO NOT USE FERTILIZER, WEED KILLER, OR APPLY PREEMERGENTS IN RAIN GARDEN AREA.
- SITE CONSTRUCTION: IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY AND LOCATE ANY EXISTING OR PROPOSED UTILITIES. ANY DAMAGE DONE BY NOT LOCATING, IS THE RESPONSIBILITY OF THE
- 2. UTILITIES SHOWN ON DRAWING ARE SCHEMATIC ONLY. REFER TO OTHER SITE DRAWINGS FOR ADDITIONAL INFORMATION AND
- COORDINATE WITH OWNER REPRESENTATIVE. 3. EROSION CONTROL SHALL BE PROVIDED DURING CONSTRUCTION


NOTE THE LOCATION OF ALL EXISTING UNDERGROUND UTILITIES IS SHOWN IN AN APPROXIMATE WAY ONLY. THE CONTRACTOR SHALL DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES BEFORE COMMENCING WORK. EXISTING GRADE INFORMATION IS APPROXIMATE. THE CONTRACTOR SHALL FIELD VERIFY EXISTING GRADES AND NOTIFY ENGINEER OF ANY DISCREPANCIES BEFORE COMMENCING WORK. CONTRACTOR AGREES TO BE FULLY RESPONSIBLE FOR ANY AND ALL DAMAGES WHICH MIGHT BE OCCASIONED BY HIS FAILURE TO CONFIRM EXISTING UTILITY AND GRADE INFORMATION.

CALL AT LEAST 2 WORKING


DAYS BEFORE YOU DIG

CALL '811'

PER CIVIL PLANS. 4. WARRANTY FOR PLANTS AND IRRIGATION IS TO BE ONE YEAR. STARTING AT FINAL ACCEPTANCE OF WORK. CONTRACTOR IS RESPONSIBLE FOR CONFIRMING IRRIGATION IS IN WORKING ORDER TO ENSURE PLANT SURVIVAL THRU WARRANTY PERIOD.



GROUNDCOVER SPACING SCALE: N.T.S.



GROUNDCOVER PLANTING DETAIL L1.1 SCALE: N.T.S.